

Dissolution Drive Belts and Kits

Dissolution Drive Belts and Kits. Select the replacement accessory by the documented specification and instrument configuration. The options below are distinct configurations; confirm the exact option, dimensions and host instrument in the quotation.



Key features

- Eight configurations of replacement belts and kits
- Minimum order quantity: 1

Technical Information

Accessory model	T-ADS-002
T-ADS-002-01	200L037 ×1 + 460L037 ×1 + 250L037 ×3
T-ADS-002-02	1.5 ×100 ×8 ×1 + 1.5 ×120 ×8 ×1 + 1.5 ×84 ×8 ×5
T-ADS-002-03	T5 ×1800 ×8 ×1 + T5 ×350 ×8 ×1
T-ADS-002-04	T5 ×1800 ×8 ×1
T-ADS-002-05	T5 ×70 ×8 ×1
T-ADS-002-06	1.5 ×84 ×8 ×5 + 1.5 ×130 ×8 ×1
T-ADS-002-07	M1.5 ×84 ×9 ×7
T-ADS-002-08	200L037 ×1 + 460L037 ×1 + 250L037 ×1

Standard Configuration

Supply of the selected accessory, in the confirmed order quantity. The host instrument and other accessories are excluded unless itemized in the quotation.

Optional Accessories

Related replacement parts are quoted separately after compatibility review. No unlisted fitting or installation service is assumed included.

Selection / Ordering Information

Include the PRECETTA instrument model, serial number, component photograph and required quantity in the inquiry. The photograph identifies the accessory type; confirm the exact ordered variant against its specification before procurement.